

C1
HAR-FLEX 12 POLES FEMALE CONNECTOR
WITH STRAIN RELIEF

C2
HAR-FLEX 12 POLES FEMALE CONNECTOR
WITH STRAIN RELIEF

WIRING TABLE


C1	WIRE	C2
1	AWG 30	1
2	AWG 30	2
3	AWG 30	3
-	AWG 30	-
11	AWG 30	11
12	AWG 30	12

HARTING P/N	REVISION	Cable length (L)
3315 243 010 0004	02	100 ± 3
3315 243 020 0005	02	200 ± 3
3315 243 050 0006	02	500 ± 5
3315 243 060 0006	00	600 ± 10
3315 243 070 0006	00	700 ± 10
3315 243 030 0006	00	300 ± 5
3315 243 005 0006	00	50 ± 3
3315 243 013 0006	00	130 ± 3
3315 243 015 0006	00	150 ± 3
3315 244 255 0006	00	255 ± 3

NOTES:

- 1.)CABLE MUST BE PERFORMED 100% CONTINUITE TEST AND HI-POT(500VDC)TEST.
- 2.)CABLE OPERATION TEMPERATURE: -20℃ TO +105℃
- 3.)CABLE SHOULD BE PACKED BY THE PLASTIC BAG,THEN PUT IT INTO THE CARTON (QTY ACCORDING TO ACTUAL CONDITION) EXPORT CARTON SHOULD BE STICKED THE LABEL WITH P/N AND QTY.
- 4.)WHITE LABEL CONTENT:

DATA CODE
HARTING P/N

		All Dimensions in mm		Tech. Character.		Free size tol.		According to production drawing	
All rights reserved		Created by ZHENGL		Inspected by WANGE		Standardisation CHENJU		Date 2018-07-11	
Department HCS - CN		Title Har-Flex 12 Pole,Dul-end,With SR,L=XX MM		State Final Release		Doc-Key / ECM-Nr. 100586793/UGD/000/H 500000137187		Rev. H	
HARTING Customised Solutions		Type TB		Number 33150002		Page 1/1			
D-32339 Espelkamp									