



C1
HAR-FLEX 26 POLE FEMALE CONNECTOR
WITH STRAIN RELIEF

C2
HAR-FLEX 26 POLE FEMALE CONNECTOR
WITH STRAIN RELIEF

WIRING TABLE

C1	WIRE	C2
1	AWG 30	1
2	AWG 30	2
3	AWG 30	3
-	AWG 30	-
25	AWG 30	25
26	AWG 30	26

HARTING P/N	REVISION	Cable length (L)
3315 243 010 0007	02	100 ± 3
3315 243 020 0008	02	200 ± 3
3315 243 050 0009	02	500 ± 5
3315 243 027 0034	02	270 ± 5
3315 243 060 0034	00	600 ± 10
3315 243 100 0034	00	1000 ± 10
3315 243 012 0034	00	120 ± 3
3315 243 017 0034	00	170 ± 3

- NOTES:
- 1.)CABLE MUST BE PERFORMED 100% CONTINUITE TEST AND HI-POT(500VDC)TEST.
 - 2.)CABLE OPERATION TEMPERATURE: -20℃ TO +105℃
 - 3.)CABLE SHOULD BE PACKED BY THE PLASTIC BAG,THEN PUT IT INTO THE CARTON (QTY ACCORDING TO ACTUAL CONDITION) EXPORT CARTON SHOULD BE STICKED THE LABEL WITH P/N AND QTY.
 - 4.)WHITE LABEL CONTENT:

DATA CODE
HARTING P/N

	All rights reserved	Scale 2:1		Free size tol.		Ref. \	
	Department HCS - CN	Created by ZHENGL		Inspected by WANGE	Standardisation CHENJU	Date 2017-11-01	State Final Release
	HARTING Customised Solutions D-32427 Minden	Title Har-Flex 26 Pole,Dul-end,With SR,L=XX MM			Doc-Key / ECM-Nr. 100587128/UGD/000/G 500000127346		
		Type TB	Number 33150003			Rev. G	Page 1/1