

Han TC350 male contact 120mm²

Series T	Specification Han TC350 male contact 120mm ² HARTING eCatalogue https://b2b.harting.com/09110006144
Category C Series T	Contacts TC 350
Category C Series T	°C 350
Category C Series T	°C 350
Series T	°C 350
Type of contact C	Crimp contact
/ersion	
Gender M	/ale
Fechnical characteristics	
Conductor cross-section 12	20 mm ²
Operating current ≤	350 A
Contact resistance ≤	0.3 mΩ
Limiting temperature -4	40 +125 °C
Stripping length 24	4 mm
Mating cycles ≥	500
Material properties	
Material (contacts) C	Copper alloy
Surface (contacts) S	Silver plated
RoHS ca	ompliant with exemption
RoHS exemptions 60	(c): Copper alloy containing up to 4 % lead by weight
ELV status co	ompliant with exemption
China RoHS 50	0
REACH Annex XVII substances N	lo
REACH ANNEX XIV substances N	lo

Page 1 / 2 | Creation date 2019-07-09 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric GmbH & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



Material properties	
REACH SVHC substances	Yes
REACH SVHC substances	Lead
Specifications and approvals	
Specifications	EN 60664-1 IEC 61984
Commercial data	
Packaging size	1
Net weight	85.5 g
Country of origin	Germany
European customs tariff number	85359000
eCl@ss	27440204 Contact for industrial connectors