

LP-Adapter Han Q 4/2



Part number	09 12 006 9901
Specification	LP-Adapter Han Q 4/2
HARTING eCatalogue	https://b2b.harting.com/09120069901

Identification

Category	Accessories
Type of accessory	PCB adapter
Description of the accessory	In the Han [®] Q 4/2

Version

Gender	Male Female
Details	for PCB's up to 2.4 mm

Technical characteristics

Rated current	30 A
Rated voltage conductor-earth	400 V
Rated voltage conductor-conductor	690 V
Rated impulse voltage	6 kV
Pollution degree	2
Rated current (signal)	7.5 A
Rated voltage (signal)	250 V
Rated impulse voltage (signal)	4 kV
Pollution degree (signal)	2
Limiting temperature	-40 ... +125 °C

Material properties

Material (insert)	LCP
RoHS	compliant with exemption



Pushing Performance

Material properties

RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	Yes
REACH SVHC substances	Lead

Specifications and approvals

UL / CSA	UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076
----------	--

Commercial data

Packaging size	1
Net weight	16.3 g
Country of origin	Romania
European customs tariff number	85366990
eCl@ss	27440402 PCB connector