

## Han Q-Data RJ45-F



Part number	09 12 011 3111
Specification	Han Q-Data RJ45-F
HARTING eCatalogue	<a href="https://b2b.harting.com/09120113111">https://b2b.harting.com/09120113111</a>

### Identification

Category	Inserts
Series	Han <sup>®</sup> Q
Identification	Data RJ45

### Version

Termination method	Crimp termination
Gender	Female
Size	Han-Compact <sup>®</sup>
Number of contacts	8
Details	Please order crimp contacts separately.

### Technical characteristics

Conductor cross-section	0.13 ... 0.52 mm <sup>2</sup>
Rated current	5 A
Rated voltage	50 V
Rated impulse voltage	0.8 kV
Pollution degree	3
Insulation resistance	>10 <sup>10</sup> Ω
Limiting temperature	-40 ... +85 °C
Mating cycles	≥500

### Material properties

Material (insert)	Polycarbonate
Colour (insert)	RAL 7032 (pebble grey)



Pushing Performance

## Material properties

Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	No

## Specifications and approvals

Specifications	EN 60664-1 IEC 61984
----------------	-------------------------

## Commercial data

Packaging size	1
Net weight	29.9 g
Country of origin	Germany
European customs tariff number	85366990
eCl@ss	27440205 Contact insert for industrial connectors