


Han-Modular coax M-contact 750hm (RG179)



| Part number | 09 14 000 6121 |
|--------------------|--|
| Specification | Han-Modular coax M-contact 750hm (RG179) |
| HARTING eCatalogue | https://b2b.harting.com/09140006121 |

Identification

| Category | Contacts |
|----------------------------|------------------------------|
| Series | DIN 41626 |
| Type of contact | Coaxial contact |
| Description of the contact | for cables RG 179 BU, 187 AU |

Version

| Termination method | Solder/crimp termination |
|--------------------|--------------------------|
| Gender | Female |

Technical characteristics

| Operating current | ≤1.5 A |
|--------------------|--------|
| Contact resistance | ≤10 mΩ |
| Impedance | 75 Ω |

Material properties

| Copper alloy |
|--|
| Gold plated |
| compliant with exemption |
| 6(c): Copper alloy containing up to 4 % lead by weight |
| compliant with exemption |
| 50 |
| No |
| No |
| Yes |
| |



Material properties

REACH SVHC substances Lead

Specifications and approvals

| Specifications | EN 60664-1 |
|----------------|------------|
| | IEC 61984 |

Commercial data

| Packaging size | 10 |
|--------------------------------|--|
| Net weight | 2.65 g |
| Country of origin | Hungary |
| European customs tariff number | 85366910 |
| eCl@ss | 27440204 Contact for industrial connectors |