

Han C module, crimp male (two part)



| | |
|--------------------|---|
| Part number | 09 14 003 3003 |
| Specification | Han C module, crimp male (two part) |
| HARTING eCatalogue | https://b2b.harting.com/09140033003 |

Identification

| | |
|---------------------------|------------------------------|
| Category | Modules |
| Series | Han-Modular® |
| Type of module | Han® C module |
| Description of the module | for increased tensile stress |

Version

| | |
|--------------------|---|
| Termination method | Crimp termination |
| Gender | Male |
| Number of contacts | 3 |
| Details | Please order crimp contacts separately. |

Technical characteristics

| | |
|--------------------------|----------------------------|
| Conductor cross-section | 1.5 ... 10 mm ² |
| Rated current | 40 A |
| Rated voltage | 500 V |
| Rated impulse voltage | 8 kV |
| Pollution degree | 3 |
| Rated current acc. to UL | 40 A |
| Rated voltage acc. to UL | 600 V |
| Insulation resistance | >10 ¹⁰ Ω |
| Limiting temperature | -40 ... +125 °C |
| Mating cycles | ≥500 |



Pushing Performance

Material properties

| | |
|---|------------------------|
| Material (insert) | Polycarbonate |
| Colour (insert) | RAL 7032 (pebble grey) |
| Material flammability class acc. to UL 94 | V-0 |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |
| REACH SVHC substances | No |

Specifications and approvals

| | |
|----------------|-------------------------|
| Specifications | EN 60664-1 IEC 61984 |
| Approvals | DNV GL |
| UL / CSA | UL 1977 ECBT2.E235076 |

Commercial data

| | |
|--------------------------------|---|
| Packaging size | 2 |
| Net weight | 13.66 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |
| eCl@ss | 27440217 Module for industrial connectors (power/signals) |