

Han D M crimp contact 0,5 mm² Au/HMC

		Part number	09 15 200 6123
		Specification	Han D M crimp contact 0,5 mm² Au/HMC
		HARTING eCatalogue	https://b2b.harting.com/09152006123
Identification			
Category	Contacts		
Series	Han D [®] HMC		
Type of contact	Crimp contact		
Version			
Gender	Male		
Technical characteristics			
Conductor cross-section	0.5 mm²		
Conductor cross-section	AWG 20		
Operating current	≤10 A		
Contact resistance	≤3 mΩ		
Stripping length	8 mm		
Mating cycles with other HMC components	≥10,000		
Material properties			
Material (contacts)	Copper alloy		
Surface (contacts)	HMC gold pla	ted	
RoHS	compliant with	n exemption	
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight		
ELV status	compliant with	n exemption	
China RoHS	50		
REACH Annex XVII substances	No		
REACH ANNEX XIV substances	No		

Page 1 / 2 | Creation date 2019-07-09 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric GmbH & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



Material properties	
REACH SVHC substances	Yes
REACH SVHC substances	Lead
Specifications and approvals	
Specifications	EN 60664-1 IEC 61984
Commercial data	
Packaging size	100
Net weight	0.66 g
Country of origin	Germany
European customs tariff number	85366990
eCl@ss	27440204 Contact for industrial connectors