

LP-ADAPTER Han DD



| | |
|--------------------|---|
| Part number | 09 16 000 9908 |
| Specification | LP-ADAPTER Han DD |
| HARTING eCatalogue | https://b2b.harting.com/09160009908 |

Identification

| | |
|------------------------------|--|
| Category | Accessories |
| Type of accessory | PCB adapter |
| Description of the accessory | In the Han DD [®] crimp insert |
| | In the Han DD [®] module |
| | In the Han [®] DDD module (different electrical data: 7.5 A 160 V 2.5 kV 3) |

Version

| | |
|---------|------------------------|
| Gender | Male |
| | Female |
| Details | for PCB's up to 2.4 mm |

Technical characteristics

| | |
|-----------------------|-----------------|
| Rated current | 7.5 A |
| Rated voltage | 250 V |
| Rated impulse voltage | 4 kV |
| Pollution degree | 3 |
| Limiting temperature | -40 ... +125 °C |

Material properties

| | |
|-----------------------------|--|
| Material (insert) | Polyamide |
| RoHS | compliant with exemption |
| RoHS exemptions | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status | compliant with exemption |
| China RoHS | 50 |
| REACH Annex XVII substances | No |



Pushing Performance

Material properties

| | |
|----------------------------|------|
| REACH ANNEX XIV substances | No |
| REACH SVHC substances | Yes |
| REACH SVHC substances | Lead |

Specifications and approvals

| | |
|----------|--|
| UL / CSA | UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076 |
|----------|--|

Commercial data

| | |
|--------------------------------|------------------------|
| Packaging size | 10 |
| Net weight | 2.49 g |
| Country of origin | Germany |
| European customs tariff number | 85366990 |
| eCl@ss | 27440402 PCB connector |