


SEK-18 SV MA STD ANG29 RKZ 10P PLS4



Part number	09 18 510 5913
Specification	SEK-18 SV MA STD ANG29 RKZ 10P PLS4
HARTING eCatalogue	https://b2b.harting.com/09185105913

Identification

Category	Connector
Series	SEK Standard
Element	Male connector
Description of the contact	Angled

Version

Termination method	Wave soldering termination
Locking type	With short levers
Connection type	PCB to cable
Number of contacts	10
Termination length	2.9 mm
Performance level	1 NM 30 (S4)

Technical characteristics

Contact rows	2
Contact spacing (termination side)	2.54 mm
Rated current	1 A
Rated voltage	500 V
Insulation resistance	$>10^9 \Omega$
Contact resistance	$\leq 20 \text{ m}\Omega$
Limiting temperature	-55 ... +125 °C
Insertion and withdrawal force	$\leq 20 \text{ N}$



Pushing Performance

Technical characteristics

Test voltage $U_{r.m.s.}$	1 kV
---------------------------	------

Material properties

Material (insert)	Thermoplastic resin (PBT)
Colour (insert)	Grey
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	No

Specifications and approvals

UL / CSA	UL 1977 ECBT2.E102079 CSA-C22.2 No. 182.3 ECBT8.E102079
----------	--

Commercial data

Packaging size	100
Net weight	4.56 g
Country of origin	Switzerland
European customs tariff number	85366953
eCl@ss	27440402 PCB connector