


SEK-18 SV MA STD STR29 RLG 50P PLS4



Part number	09 18 550 5904
Specification	SEK-18 SV MA STD STR29 RLG 50P PLS4
HARTING eCatalogue	https://b2b.harting.com/09185505904

Identification

Category	Connector
Series	SEK Standard
Element	Male connector
Description of the contact	Straight

Version

Termination method	Wave soldering termination
Locking type	With long levers
Connection type	PCB to cable
Number of contacts	50
Termination length	2.9 mm
Performance level	1 NM 30 (S4)

Technical characteristics

Contact rows	2
Contact spacing (termination side)	2.54 mm
Rated current	1 A
Rated voltage	500 V
Insulation resistance	$>10^9 \Omega$
Contact resistance	$\leq 20 \text{ m}\Omega$
Limiting temperature	-55 ... +125 °C
Insertion and withdrawal force	$\leq 100 \text{ N}$



Pushing Performance

Technical characteristics

Test voltage $U_{r,m.s.}$	1 kV
---------------------------	------

Material properties

Material (insert)	Thermoplastic resin (PBT)
Colour (insert)	Grey
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	No

Specifications and approvals

UL / CSA	UL 1977 ECBT2.E102079 CSA-C22.2 No. 182.3 ECBT8.E102079
----------	--

Commercial data

Packaging size	50
Net weight	11.02 g
Country of origin	Switzerland
European customs tariff number	85366953
eCl@ss	27440402 PCB connector