

Han 3A-AK-Dichtung



Part number	09 20 003 5425
Specification	Han 3A-AK-Dichtung
HARTING eCatalogue	https://b2b.harting.com/09200035425

Identification

Category	Hoods/Housings
Series of hoods/housings	Han A [®]
Type of hood/housing	Protection cover
	for bulkhead mounted housings
	for bulkhead mounted housings for surface mounted housings
Description of hood/housing	
Description of hood/housing	for surface mounted housings

Version

Locking type	Single locking lever
Size	3 A
Field of application	Standard Hoods/housings for industrial applications
Details	for mounted female insert or for mounted Han-Brid [®] insert

Technical characteristics

Limiting temperature	-40 +125 °C
Degree of protection acc. to IEC 60529	IP44 IP65 / IP67 with seal screw 09 20 000 9918
Type rating acc. to UL 50 / UL 50E	12

Material properties

Material (seal)	NBR
RoHS	compliant
ELV status	compliant



Material properties

China RoHS	е
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	No

Specifications and approvals

Approvals	DNV GL	
-----------	--------	--

Commercial data

Packaging size	10
Net weight	23 g
Country of origin	Romania
European customs tariff number	85389099
eCl@ss	27440208 Cap for industrial connectors