

Han 24B split hood



Part number	09 30 024 0498
Specification	Han 24B split hood
HARTING eCatalogue	https://b2b.harting.com/09300240498

Identification

RoHS

ELV status

Category	Hoods/Housings
Series of hoods/housings	Han [®] B
Type of hood/housing	Panel feed through housing
Туре	High construction
Version	
Locking type	Double locking lever
Size	24 B
Version	Top entry
Cable entry	4x
Field of application	Standard hoods/housings for industrial connectors
Details	Please order cable entry seals separately.
Pack contents	2 split hood halves 3x M4 screw
Technical characteristics	
Limiting temperature	-40 +125 °C
Degree of protection acc. to IEC 60529	IP65
Material properties	
Material (hood/housing)	Aluminium die-cast
Material (seal)	NBR

Page 1 / 2 | Creation date 2019-09-17 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric GmbH & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com

compliant

compliant



Material properties

China RoHS	e
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	No
Commercial data	
Packaging size	1
Net weight	181 g
Country of origin	China
European customs tariff number	8538900000
eCl@ss	27440202 Shell for industrial connectors