

Terminal housing f. motor Han 10B 80, wi



| | |
|--------------------|---|
| Part number | 09 30 410 0901 |
| Specification | Terminal housing f. motor Han 10B 80, wi |
| HARTING eCatalogue | https://b2b.harting.com/09304100901 |

Identification

| | |
|--------------------------|-------------------------------|
| Category | Hoods/Housings |
| Series of hoods/housings | Han-Drive® |
| Type of hood/housing | Housing for motor application |

Version

| | |
|----------------|----------------------|
| Locking type | Single locking lever |
| Han-Easy Lock® | Yes |
| Size | 10 B |

Technical characteristics

| | |
|--|-----------------|
| Limiting temperature | -40 ... +125 °C |
| Degree of protection acc. to IEC 60529 | IP65 |
| Type rating acc. to UL 50 / UL 50E | 4 4X 12 |
| Distance assembly fixing holes | 68 mm |

Material properties

| | |
|-------------------------|----------------------------------|
| Material (hood/housing) | Aluminium die-cast |
| Surface (hood/housing) | Uncoated |
| Material (seal) | NBR |
| Material (locking) | Polycarbonate Stainless steel |
| Colour (locking) | RAL 7037 (dust grey) |



Pushing Performance

Material properties

Material flammability class acc. to UL 94 (locking levers) V-0

RoHS compliant

ELV status compliant

China RoHS e

REACH Annex XVII substances No

REACH ANNEX XIV substances No

REACH SVHC substances No

Specifications and approvals

Approvals DNV GL

Commercial data

Packaging size 1

Net weight 251.6 g

Country of origin Germany

European customs tariff number 85389099

eCl@ss 27440202 Shell for industrial connectors