

## SCRJ POF IP20 Plug



Part number	09 35 002 4002
Specification	SCRJ POF IP20 Plug
HARTING eCatalogue	<a href="https://b2b.harting.com/09350024002">https://b2b.harting.com/09350024002</a>
Features	Intuitive locking mechanism

### Identification

Category	Connector
Series	Han <sup>®</sup> PushPull (V14)
Identification	SCRJ
Element	Connector set
Specification	AIDA compliant 1 mm POF

### Version

Termination method	Fast termination
Locking type	PushPull
Number of contacts	2

### Technical characteristics

Wire outer diameter	≤2.2 mm
Ferrule diameter	2.5 mm
Limiting temperature	-40 ... +70 °C
Mating cycles	≥750
Degree of protection acc. to IEC 60529	IP20

### Material properties

Material (hood/housing)	Thermoplastic
Colour (hood/housing)	Black
Material flammability class acc. to UL 94	V-0
RoHS	compliant with exemption



## Material properties

RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	Yes
REACH SVHC substances	Lead

## Specifications and approvals

Specifications	IEC 61076-3-117 Variant 14 (V14) IEC 61754-24 Mating face
UL / CSA	UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076
PROFINET	Yes

## Commercial data

Packaging size	1
Net weight	16.25 g
Country of origin	Germany
European customs tariff number	85389099
eCl@ss	27440205 Contact insert for industrial connectors