

## Han PushPull RJ45 Genderchanger



Part number	09 35 221 0501
Specification	Han PushPull RJ45 Genderchanger
HARTING eCatalogue	<a href="https://b2b.harting.com/09352210501">https://b2b.harting.com/09352210501</a>
Features	Intuitive locking mechanism

### Identification

Category	Connectors
Series	Han® PushPull (V14)
Identification	RJ45
Element	Gender changer
Specification	AIDA compliant

### Version

Locking type	PushPull
Fixing	Wall mountable with 4 screws type M5

### Technical characteristics

Conductor cross-section	0.22 ... 0.32 mm <sup>2</sup> Stranded 0.26 ... 0.32 mm <sup>2</sup> Solid
Rated current	1.75 A
Rated voltage	50 V
Limiting temperature	-40 ... +70 °C
Mating cycles	≥750
Degree of protection acc. to IEC 60529	IP65 when mated IP67 when mated
Transmission characteristics	Cat. 6 Class E up to 250 MHz

### Material properties

Material (hood/housing)	Aluminium
Surface (hood/housing)	Anodised
Material flammability class acc. to UL 94	V-0



Pushing Performance

## Material properties

RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	No

## Specifications and approvals

Specifications	IEC 61076-3-117 Variant 14 (V14) IEC 60603-7 Mating face
UL / CSA	UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076
PROFINET	Yes

## Commercial data

Packaging size	1
Net weight	124.25 g
Country of origin	Germany
European customs tariff number	85389099
eCl@ss	27440190 Industry connector (unspecified)