


Han Ex-C for HCC Han 3A with seal



Part number	09 36 003 5409
Specification	Han Ex-C for HCC Han 3A with seal
HARTING eCatalogue	https://b2b.harting.com/09360035409

Identification

Category	Hoods/Housings
Series of hoods/housings	Han [®] Ex
Type of hood/housing	Protection cover
Description of hood/housing	for cable to cable housing Metal With fixing cord With seal

Version

Locking type	Single locking lever
Size	3 A
Field of application	Connectors for explosion hazardous environments
Details	for mounted female insert
Details	ATTENTION! Only to be used with Han [®] Ex hoods and housings!

Technical characteristics

Limiting temperature	-20 ... +40 °C
Degree of protection acc. to IEC 60529	IP65 With cable gland

Material properties

Material (hood/housing)	Zinc die-cast
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 5015 (sky blue)
Material (seal)	NBR
RoHS	compliant



Pushing Performance

Material properties

ELV status	compliant
China RoHS	e
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	No

Commercial data

Packaging size	10
Net weight	23.4 g
Country of origin	Germany
European customs tariff number	85389099
eCl@ss	27440202 Shell for industrial connectors