


Han Ex-C for HCC Han 3A



Part number	09 36 003 5410
Specification	Han Ex-C for HCC Han 3A
HARTING eCatalogue	https://b2b.harting.com/09360035410

Identification

RoHS

ELV status

Category	Hoods/Housings
Series of hoods/housings	Han [®] Ex
Type of hood/housing	Protection cover
Description of hood/housing	for cable to cable housing Metal With fixing cord
Version	
Locking type	Single locking lever
Size	3 A
Field of application	Connectors for explosion hazardous environments
Details	for mounted male insert
Details	ATTENTION! Only to be used with Han [®] Ex hoods and housings!
Technical characteristics	
Limiting temperature	-20 +40 °C
Degree of protection acc. to IEC 60529	IP65 With cable gland
Material properties	
Material (hood/housing)	Zinc die-cast
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 5015 (sky blue)

Page 1 / 2 | Creation date 2019-09-05 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric GmbH & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com

compliant

compliant

Product data sheet 09 36 003 5410 Han Ex-C for HCC Han 3A



Material properties

China RoHS	e
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	No
Commercial data	
Packaging size	10
Net weight	22.5 g
Country of origin	Germany
European customs tariff number	85389099
eCl@ss	27440202 Shell for industrial connectors