

Han 3HPR angled hous. long version



| Part number | 09 40 003 0953 |
|--------------------|-------------------------------------|
| Specification | Han 3HPR angled hous. long version |
| HARTING eCatalogue | https://b2b.harting.com/09400030953 |

Identification

| Category | Hoods/Housings |
|-----------------------------|-------------------------------------|
| Series of hoods/housings | Han [®] HPR |
| Type of hood/housing | Bulkhead mounted housing |
| Description of hood/housing | Angled |
| | Long version |
| | Open bottom |
| | Tapped blind hole for fixing screws |

Version

| Locking type | Screw locking |
|----------------------|---|
| Size | 3 A |
| Field of application | Hoods/housings for harsh outdoor environments |
| Pack contents | With seal screw |

Technical characteristics

| Limiting temperature | -40 +125 °C |
|--|--|
| Tightening torque (screw locking) | 2 Nm |
| Degree of protection acc. to IEC 60529 | IP65 IP68 IP69 / IPX9K acc. to ISO 20653 |
| Type rating acc. to UL 50 / UL 50E | 4 4X 12 |

Material properties

| Material (hood/housing) Zinc die-cast |
|---------------------------------------|
|---------------------------------------|



Material properties

| Surface (hood/housing) | Chromated |
|-----------------------------|----------------------|
| Colour (hood/housing) | RAL 9005 (jet black) |
| Material (seal) | NBR |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | е |
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |
| REACH SVHC substances | No |

Specifications and approvals

| Approvals | DNV GL |
|-----------|--|
| UL / CSA | UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076 |

Commercial data

| Packaging size | 1 |
|--------------------------------|--|
| Net weight | 216 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |
| eCl@ss | 27440202 Shell for industrial connectors |