

Han 24HPR EasyCon cover without entry



| | |
|--------------------|---|
| Part number | 09 40 024 9908 |
| Specification | Han 24HPR EasyCon cover without entry |
| HARTING eCatalogue | https://b2b.harting.com/09400249908 |

Identification

| | |
|-----------------------------|---|
| Category | Hoods/Housings |
| Series of hoods/housings | Han [®] HPR EasyCon |
| Type of hood/housing | Mounting cover |
| Description of hood/housing | for surface mounted housings for hoods |

Version

| | |
|----------------------|---|
| Locking type | Screw locking |
| Size | 24 HPR |
| Field of application | Hoods/housings for harsh outdoor environments |

Technical characteristics

| | |
|--|--------------------------------|
| Limiting temperature | -40 ... +125 °C |
| Tightening torque | 6 Nm Mounting cover |
| | 6 Nm Distance bolt |
| | 6 Nm Fixing screws |
| Degree of protection acc. to IEC 60529 | IP65 |
| | IP68 |
| | IP69 / IPX9K acc. to ISO 20653 |
| Type rating acc. to UL 50 / UL 50E | 4 |
| | 4X |
| | 12 |

Material properties

| | |
|-------------------------|---|
| Material (hood/housing) | Aluminium die-cast Corrosion resistant |
| Surface (hood/housing) | Powder-coated |



Pushing Performance

Material properties

| | |
|-----------------------------|----------------------|
| Colour (hood/housing) | RAL 9005 (jet black) |
| Material (seal) | NBR |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |
| REACH SVHC substances | No |

Specifications and approvals

| | |
|-----------|--|
| Approvals | DNV GL |
| UL / CSA | UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076 |

Commercial data

| | |
|--------------------------------|--|
| Packaging size | 1 |
| Net weight | 284 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |
| eCl@ss | 27440208 Cap for industrial connectors |