

Han3A RJ45 10G Cat6 PFT insert 8p



| | |
|--------------------|---|
| Part number | 09 45 200 1560 |
| Specification | Han3A RJ45 10G Cat6 PFT insert 8p |
| HARTING eCatalogue | https://b2b.harting.com/09452001560 |

Identification

| | |
|----------|------------|
| Category | Connectors |
| Series | RJ45 |
| Element | Inserts |

Version

| | |
|-----------|--|
| Size | Han [®] 3 A |
| Shielding | Fully shielded, 360° shielding contact |

Technical characteristics

| | |
|------------------------------|--|
| Limiting temperature | -40 ... +70 °C |
| Mating cycles | ≥500 |
| Transmission characteristics | Cat. 6 Class E up to 250 MHz |
| Data rate | 10 Mbit/s 100 Mbit/s 1 Gbit/s 10 Gbit/s |

Material properties

| | |
|-----------------------------|-----------|
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |
| REACH SVHC substances | No |



Pushing Performance

Specifications and approvals

| | |
|----------|--|
| UL / CSA | UL 1977 ECBT2.E102079 CSA-C22.2 No. 182.3 ECBT8.E102079 |
| PROFINET | Yes |

Commercial data

| | |
|--------------------------------|---|
| Packaging size | 1 |
| Net weight | 26 g |
| Country of origin | Romania |
| European customs tariff number | 85366990 |
| eCl@ss | 27440205 Contact insert for industrial connectors |