

# HPP V4 RJ45 coupler Cat.6



Part number	09 45 345 1560
Specification	HPP V4 RJ45 coupler Cat.6
HARTING eCatalogue	https://b2b.harting.com/09453451560

#### Identification

Category	Connector
Series	HARTING PushPull (V4)
Identification	RJ45
Element	Coupler

### Version

Locking type	PushPull
Shielding	Fully shielded, 360° shielding contact
Number of contacts	8

## **Technical characteristics**

Limiting temperature	-40 +70 °C
Mating cycles	≥750
Degree of protection acc. to IEC 60529	IP65 IP67
Transmission characteristics	Cat. 6 Class E up to 250 MHz
Data rate	10 Mbit/s 100 Mbit/s 1 Gbit/s 10 Gbit/s

## Material properties

Material (hood/housing)	Thermoplastic
Colour (hood/housing)	Black
Material flammability class acc. to UL 94	V-0

Page 1 / 2 | Creation date 2019-09-19 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com



## Material properties

RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	No

## Specifications and approvals

Specifications	IEC 61076-3-106 Variant 4 (V4)
Commercial data	
Packaging size	1
Net weight	37.5 g
Country of origin	Romania
European customs tariff number	85366990
eCl@ss	27440190 Industry connector (unspecified)