

Han3A RJ45 Hybrid power jack SMD T&R



Part number	09 45 525 0041
Specification	Han3A RJ45 Hybrid power jack SMD T&R
HARTING eCatalogue	https://b2b.harting.com/09455250041

Identification

Category	Connector
Series	RJ45 Hybrid
Element	Power module
Specification	for direct device integration

Version

Termination method	Reflow soldering termination (SMT)
Size	Han [®] 3 A
Number of contacts	0
Additional contacts	4x 48 V
Pack contents	100 pieces on reel

Technical characteristics

Conductor cross-section	1.5 mm ²
Limiting temperature	-40 +70 °C
Mating cycles	≥500

Material properties

RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No

Page 1 / 2 | Creation date 2019-09-19 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com



Material properties	
REACH SVHC substances	No
Specifications and approvals	
PROFINET	Yes
Commercial data	
Packaging size	100
Net weight	7.39 g
Country of origin	Romania
European customs tariff number	85366990
eCl@ss	27440205 Contact insert for industrial connectors