

Han-Yellock module M-c, blue



Part number	11 05 105 3011
Specification	Han-Yellock module M-c, blue
HARTING eCatalogue	https://b2b.harting.com/11051053011

Identification

Category	Inserts
Series	Han-Yellock®
Element	Module

Version

Termination method	Crimp termination
Gender	Male
Number of contacts	5

Technical characteristics

Conductor cross-section	0.14 ... 4 mm ²
Rated current	20 A
Rated voltage	500 V
Rated impulse voltage	6 kV
Pollution degree	3
Insulation resistance	>10 ¹⁰ Ω
Contact resistance	≤2 mΩ
Limiting temperature	-40 ... +125 °C
Mating cycles	≥500

Material properties

Material (insert)	Polycarbonate
Colour (insert)	RAL 5015 (sky blue)
Material (contacts)	Copper alloy



Pushing Performance

Material properties

Surface (contacts)	Silver plated
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	No

Specifications and approvals

Specifications	EN 60664-1 IEC 61984
Approvals	DNV GL

Commercial data

Packaging size	2
Net weight	4.94 g
Country of origin	Germany
European customs tariff number	85389099
eCl@ss	27440205 Contact insert for industrial connectors