

Han-Yellock 30 bulkhead housing



| | |
|--------------------|---|
| Part number | 11 13 300 0301 |
| Specification | Han-Yellock 30 bulkhead housing |
| HARTING eCatalogue | https://b2b.harting.com/11133000301 |

Identification

| | |
|--------------------------|--------------------------|
| Category | Hoods/Housings |
| Series of hoods/housings | Han-Yellock® |
| Type of hood/housing | Bulkhead mounted housing |

Version

| | |
|----------------------|---|
| Size | Han-Yellock® 30 |
| Field of application | Hoods/housings for outdoor applications |

Technical characteristics

| | |
|--|-----------------|
| Limiting temperature | -40 ... +125 °C |
| Un-/locking temperature | -10 ... +85 °C |
| Degree of protection acc. to IEC 60529 | IP65 IP67 |

Material properties

| | |
|-----------------------------|----------------------|
| Material (hood/housing) | Zinc die-cast |
| Surface (hood/housing) | Passivated |
| Colour (hood/housing) | RAL 9005 (jet black) |
| Material (seal) | NBR |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |



Pushing Performance

Material properties

REACH SVHC substances No

Specifications and approvals

| | |
|----------------|-------------------------|
| Specifications | EN 60664-1 IEC 61984 |
|----------------|-------------------------|

| | |
|-----------|--------|
| Approvals | DNV GL |
|-----------|--------|

Commercial data

| | |
|----------------|---|
| Packaging size | 1 |
|----------------|---|

| | |
|------------|----------|
| Net weight | 110.98 g |
|------------|----------|

| | |
|-------------------|---------|
| Country of origin | Germany |
|-------------------|---------|

| | |
|--------------------------------|----------|
| European customs tariff number | 85389099 |
|--------------------------------|----------|

| | |
|--------|--|
| eCl@ss | 27440202 Shell for industrial connectors |
|--------|--|
