

# Han-Yellock 60M carrier hood btn plain



Part number	11 13 600 0100
Specification	Han-Yellock 60M carrier hood btn plain
HARTING eCatalogue	https://b2b.harting.com/11136000100

## Identification

Category	Hoods/Housings
Series of hoods/housings	Han-Yellock <sup>®</sup>
Type of hood/housing	Carrier hood
Description of hood/housing	Plain push button

## Version

Locking type	Push button
Size	Han-Yellock <sup>®</sup> 60
Field of application	Hoods/housings for outdoor applications

# **Technical characteristics**

Limiting temperature	-40 +125 °C
Un-/locking temperature	-10 +85 °C
Mating cycles	≥500
Degree of protection acc. to IEC 60529	IP65
	IP67

# Material properties

Material (hood/housing)	Zinc die-cast
Surface (hood/housing)	Passivated
Colour (hood/housing)	RAL 9005 (jet black)
Material (seal)	NBR
Material (locking)	Polyamide Stainless steel

Page 1 / 2 | Creation date 2019-07-09 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric GmbH & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



## Material properties

Colour (locking)	Melon yellow
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	No

## Specifications and approvals

Specifications	EN 60664-1 IEC 61984
Approvals	DNV GL

# Commercial data

Packaging size	1
Net weight	255 g
Country of origin	Germany
European customs tariff number	85389099
eCl@ss	27440202 Shell for industrial connectors