

Han CGM-P M20x1,5 D.10-14mm black



| | |
|--------------------|---|
| Part number | 19 00 000 5185 |
| Specification | Han CGM-P M20x1,5 D.10-14mm black |
| HARTING eCatalogue | https://b2b.harting.com/19000005185 |

Identification

| | |
|--------------------------|-------------|
| Category | Accessories |
| Series of hoods/housings | Han® CGM-P |
| Type of accessory | Cable gland |

Technical characteristics

| | |
|--|--|
| Limiting temperature | -40 ... +100 °C |
| Tightening torque | 4.5 Nm |
| Wrench size | 27 |
| Degree of protection acc. to IEC 60529 | IP68 IP69 / IPX9K acc. to ISO 20653 |
| Size | M20 |
| Clamping range | 10 ... 14 mm |
| Width across corners | 29.8 mm |

Material properties

| | |
|---|----------------------|
| Material (seal) | NBR |
| Material (cable glands) | Polyamide |
| Colour (accessories) | RAL 9005 (jet black) |
| Material flammability class acc. to UL 94 | V-0 |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |



Pushing Performance

Material properties

REACH SVHC substances No

Specifications and approvals

| | |
|-----------|--|
| Approvals | DNV GL |
| UL / CSA | UL 514B QCRV.E479780 CSA-C22.2 No. 18.3 QCRV7.E479780 |

Commercial data

| | |
|--------------------------------|--|
| Packaging size | 10 |
| Net weight | 14.3 g |
| Country of origin | Germany |
| European customs tariff number | 84849000 |
| eCl@ss | 27144432 Screwed cable gland (electr.) |