

Han CGM-P-EXi M25 D 9...16mm



| | |
|--------------------|---|
| Part number | 19 00 000 7104 |
| Specification | Han CGM-P-EXi M25 D 9...16mm |
| HARTING eCatalogue | https://b2b.harting.com/19000007104 |

Identification

| | |
|--------------------------|---------------|
| Category | Accessories |
| Series of hoods/housings | Han® CGM-Ex i |
| Type of accessory | Cable gland |

Version

| | |
|----------------------|--------------------------------------|
| Field of application | Intrinsically safe electric circuits |
|----------------------|--------------------------------------|

Technical characteristics

| | |
|--|--|
| Limiting temperature | -40 ... +100 °C |
| Tightening torque | 5 Nm |
| Wrench size | 33 |
| Degree of protection acc. to IEC 60529 | IP68 IP69 / IPX9K acc. to ISO 20653 |
| Size | M25 |
| Clamping range | 9 ... 16 mm |
| Width across corners | 33.5 mm |

Material properties

| | |
|---|---|
| Material (seal) | NBR |
| Material (cable glands) | Polyamide |
| Colour (accessories) | RAL 5012 (light blue) RAL 9005 (jet black) |
| Material flammability class acc. to UL 94 | V-0 |
| RoHS | compliant |
| ELV status | compliant |



Pushing Performance

Material properties

| | |
|-----------------------------|----|
| China RoHS | e |
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |
| REACH SVHC substances | No |

Specifications and approvals

| | |
|-----------|--------|
| Approvals | DNV GL |
|-----------|--------|

Commercial data

| | |
|--------------------------------|--|
| Packaging size | 1 |
| Net weight | 23.38 g |
| Country of origin | Germany |
| European customs tariff number | 39269097 |
| eCl@ss | 27144432 Screwed cable gland (electr.) |