

Han Compact-gg-M25-EMC



Part number	19 12 008 0412
Specification	Han Compact-gg-M25-EMC
HARTING eCatalogue	https://b2b.harting.com/19120080412

Identification

Category	Hoods/Housings
Series of hoods/housings	Han-Compact [®]
Type of hood/housing	Hood
Description of hood/housing	for Han-Compact [®] half cable gland With separate PE terminating point for all inserts of size Han-Compact [®]
Version	
Locking type	Single locking lever
Size	Han-Compact [®]
Version	Top entry
Cable entry	1x M25
Field of application	Hoods/Housings for higher EMC requirements
Technical characteristics	
Limiting temperature	-40 +125 °C
Degree of protection acc. to IEC 60529	IP65
Material properties	
Material (hood/housing)	Zinc die-cast
Surface (hood/housing)	Nickel plated
RoHS	compliant
ELV status	compliant
China RoHS	e

Page 1 / 2 | Creation date 2019-08-06 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric GmbH & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com

Product data sheet 19 12 008 0412 Han Compact-gg-M25-EMC



Material properties

REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	No
Specifications and approvals	
Approvals	DNV GL
Commercial data	
Packaging size	1
Net weight	198.8 g
Country of origin	Germany
European customs tariff number	85389099
eCl@ss	27440202 Shell for industrial connectors