

Han Compact Top Entry Hood M25 HC nickel



| | |
|--------------------|---|
| Part number | 19 12 008 0428 |
| Specification | Han Compact Top Entry Hood M25 HC nickel |
| HARTING eCatalogue | https://b2b.harting.com/19120080428 |

Identification

| | |
|-----------------------------|--|
| Category | Hoods/Housings |
| Series of hoods/housings | Han-Compact® |
| Type of hood/housing | Hood |
| Description of hood/housing | for standard cable gland With separate PE terminating point for all inserts of size Han-Compact® |

Version

| | |
|----------------------|--|
| Locking type | Single locking lever |
| Size | Han-Compact® |
| Version | Top entry |
| Cable entry | 1x M25 |
| Field of application | Hoods/Housings for higher EMC requirements |

Technical characteristics

| | |
|--|-----------------|
| Limiting temperature | -40 ... +125 °C |
| Degree of protection acc. to IEC 60529 | IP65 |

Material properties

| | |
|-------------------------|---------------|
| Material (hood/housing) | Zinc die-cast |
| Surface (hood/housing) | Nickel plated |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |



Pushing Performance

Material properties

| | |
|-----------------------------|----|
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |
| REACH SVHC substances | No |

Specifications and approvals

| | |
|-----------|--------|
| Approvals | DNV GL |
|-----------|--------|

Commercial data

| | |
|--------------------------------|--|
| Packaging size | 1 |
| Net weight | 313 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |
| eCl@ss | 27440202 Shell for industrial connectors |