

## Han 22HPR slim HTE-S-3xM25



Part number	19 40 022 0461
Specification	Han 22HPR slim HTE-S-3xM25
HARTING eCatalogue	<a href="https://b2b.harting.com/19400220461">https://b2b.harting.com/19400220461</a>

### Identification

Category	Hoods/Housings
Series of hoods/housings	Han <sup>®</sup> HPR slim
Type of hood/housing	Hood

### Version

Locking type	Screw locking
Size	22 HPR
Version	Top entry
Cable entry	3x M25
Field of application	Hoods/housings for harsh environments

### Technical characteristics

Limiting temperature	-40 ... +125 °C
Tightening torque (screw locking)	4 Nm
Tightening torque	10 Nm Fixing screws
	15 Nm PE screw
Degree of protection acc. to IEC 60529	IP66
	IP68
	IP69 / IPX9K acc. to ISO 20653

### Material properties

Material (hood/housing)	Aluminium die-cast
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 9005 (jet black)
Material (locking)	Stainless steel



Pushing Performance

## Material properties

RoHS	compliant with exemption
RoHS exemptions	6(a) / 6(a)-I: Lead as an alloying element in steel for machining purposes and in galvanised steel containing up to 0,35 % lead by weight / Lead as an alloying element in steel for machining purposes containing up to 0,35 % lead by weight and in batch hot dip galvanised steel components containing up to 0,2 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	Yes
REACH SVHC substances	Lead

## Specifications and approvals

Specifications	IEC 61984 EN 60664-1
----------------	-------------------------

## Commercial data

Packaging size	1
Net weight	882 g
Country of origin	China
European customs tariff number	85389099
eCl@ss	27440202 Shell for industrial connectors