

Han 22HPR-HSG-S-4xM20



Part number	19 40 022 0970
Specification	Han 22HPR-HSG-S-4xM20
HARTING eCatalogue	https://b2b.harting.com/19400220970

Identification

Category	Hoods/Housings
Series of hoods/housings	Han® HPR slim
Type of hood/housing	Surface mounted housing

Version

Locking type	Screw locking
Size	22 HPR
Version	Top entry
Cable entry	4x M20
Field of application	Hoods/housings for harsh environments

Technical characteristics

Limiting temperature	-40 ... +125 °C
Tightening torque (screw locking)	4 Nm
Tightening torque	10 Nm Fixing screws 15 Nm PE screw
Degree of protection acc. to IEC 60529	IP66 IP68 IP69 / IPX9K acc. to ISO 20653

Material properties

Material (hood/housing)	Aluminium die-cast
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 9005 (jet black)
Material (seal)	NBR



Pushing Performance

Material properties

Material (locking)	Stainless steel
RoHS	compliant with exemption
RoHS exemptions	6(a) / 6(a)-I: Lead as an alloying element in steel for machining purposes and in galvanised steel containing up to 0,35 % lead by weight / Lead as an alloying element in steel for machining purposes containing up to 0,35 % lead by weight and in batch hot dip galvanised steel components containing up to 0,2 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	Yes
REACH SVHC substances	Lead

Specifications and approvals

Specifications	IEC 61984 EN 60664-1
----------------	-------------------------

Commercial data

Packaging size	1
Net weight	838 g
Country of origin	China
European customs tariff number	8538900000
eCl@ss	27440202 Shell for industrial connectors