

Han 24HPR EasyCon Cover 3xM40

J			
		Part number	19 40 024 9907
		Specification	Han 24HPR EasyCon Cover 3xM40
		HARTING eCatalogue	https://b2b.harting.com/19400249907
Identification			
Category	Hoods/Housi	ngs	
Series of hoods/housings	Han [®] HPR E	asyCon	
Type of hood/housing	Mounting cov	ver	
Description of hood/housing		for surface mounted housings for hoods	
	IOI HOOUS		
Version			
Locking type	Screw locking	g	
Size	24 HPR		
Cable entry	3x M40		
Field of application	Hoods/housir	ngs for harsh outdoor envir	onments
Technical characteristics			
Limiting temperature	-40 +125 °	С	
	6 Nm Mounti		
Tightening torque	6 Nm Distand	ce bolt	
	6 Nm Fixing	screws	
Degree of protection acc. to IEC 60529	IP65 IP68		
		acc. to ISO 20653	
Type rating acc. to UL 50 / UL 50E	4 4X		
	12		
Material properties			
Material properties	مار رومین ایر میں الم	o oost	
Material (hood/housing)	Aluminium di Corrosion res		

Page 1 / 2 | Creation date 2019-07-09 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric GmbH & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



Material properties

Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 9005 (jet black)
Material (seal)	NBR

Specifications and approvals

Approvals	DNV GL
UL / CSA	UL 1977 ECBT2.E235076
	CSA-C22.2 No. 182.3 ECBT8.E235076

Commercial data

Packaging size	1
Net weight	208 g
Country of origin	Germany
European customs tariff number	85389099
eCl@ss	27440208 Cap for industrial connectors