

Han-Eco Mod.16-HTE-M40



| | |
|--------------------|---|
| Part number | 19 41 016 0423 |
| Specification | Han-Eco Mod.16-HTE-M40 |
| HARTING eCatalogue | https://b2b.harting.com/19410160423 |

Identification

| | |
|--------------------------|------------------|
| Category | Hoods/Housings |
| Series of hoods/housings | Han-Eco® Modular |
| Type of hood/housing | Hood |

Version

| | |
|--------------|----------------------|
| Locking type | Double locking lever |
| Size | 16 B |
| Version | Top entry |
| Cable entry | 1x M40 |

Technical characteristics

| | |
|--|-----------------|
| Limiting temperature | -40 ... +125 °C |
| Number of relockings | ≥500 |
| Degree of protection acc. to IEC 60529 | IP65 |

Material properties

| | |
|---|-------------------------------------|
| Material (hood/housing) | Polyamide Fibre-glass reinforced |
| Colour (hood/housing) | RAL 9005 (jet black) |
| Material flammability class acc. to UL 94 | V-0 |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | No |



Pushing Performance

Material properties

REACH ANNEX XIV substances No

REACH SVHC substances No

Specifications and approvals

Specifications IEC 61984
EN 45545-2 R22: HL1, HL2, HL3
EN 45545-2 R23: HL1, HL2, HL3
EN 45545-2 R24: HL1, HL2, HL3

UL / CSA UL 1977 ECBT2.E235076
CSA-C22.2 No. 182.3 ECBT8.E235076

Commercial data

Packaging size 1
Net weight 155.4 g
Country of origin Germany
European customs tariff number 85389099
eCl@ss 27440202 Shell for industrial connectors