

## Han-Eco 16B Outd-HSM2-with SL-M40



Part number	19 43 216 0293
Specification	Han-Eco 16B Outd-HSM2-with SL-M40
HARTING eCatalogue	<a href="https://b2b.harting.com/19432160293">https://b2b.harting.com/19432160293</a>

### Identification

Category	Hoods/Housings
Series of hoods/housings	Han-Eco® B
Type of hood/housing	Surface mounted housing

### Version

Locking type	Single locking lever
Size	16 B
Version	Side entry
Cable entry	2x M40

### Technical characteristics

Limiting temperature	-40 ... +125 °C
Number of relockings	≥500
Degree of protection acc. to IEC 60529	IP66

### Material properties

Material (hood/housing)	Polyamide Fibre-glass reinforced
Colour (hood/housing)	RAL 9005 (jet black)
Material (seal)	FPM
Colour (seal)	RAL 7001 (silver-grey)
Material (locking)	Polyamide Fibre-glass reinforced
Colour (locking)	RAL 9005 (jet black)
Material flammability class acc. to UL 94	V-0



Pushing Performance

## Material properties

Material flammability class acc. to UL 94  
 (locking levers) V-0

RoHS compliant

ELV status compliant

China RoHS e

REACH Annex XVII substances No

REACH ANNEX XIV substances No

REACH SVHC substances No

## Specifications and approvals

Specifications IEC 61984  
 EN 45545-2 R22: HL1, HL2, HL3  
 EN 45545-2 R23: HL1, HL2, HL3  
 EN 45545-2 R24: HL1, HL2, HL3

## Commercial data

Packaging size 1

Net weight 179 g

Country of origin Germany

European customs tariff number 85389099

eCI@ss 27440202 Shell for industrial connectors