

Han 16EMC/B-HTE2/HSE-M20/M32 (HT)



| | |
|--------------------|---|
| Part number | 19 62 816 0529 |
| Specification | Han 16EMC/B-HTE2/HSE-M20/M32 (HT) |
| HARTING eCatalogue | https://b2b.harting.com/19628160529 |

Identification

| | |
|--------------------------|--|
| Category | Hoods/Housings |
| Series of hoods/housings | Han [®] EMC/B Han [®] High Temp |
| Type of hood/housing | Hood |
| Type | High construction |

Version

| | |
|----------------------|--|
| Locking type | Double locking lever |
| Size | 16 B |
| Version | Top/side entry |
| Cable entry | 2x M20 1x M32 |
| Field of application | Hoods/Housings for higher EMC requirements |

Technical characteristics

| | |
|--|---|
| Limiting temperature | -40 ... +125 °C -40 ... +200 °C With Han [®] High Temp components |
| Degree of protection acc. to IEC 60529 | IP65 |
| Type rating acc. to UL 50 / UL 50E | 4 12 |

Material properties

| | |
|-------------------------|--------------------|
| Material (hood/housing) | Aluminium die-cast |
| Surface (hood/housing) | Uncoated |
| Colour (hood/housing) | Unpainted |



Pushing Performance

Material properties

| | |
|-----------------------------|-----------|
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |
| REACH SVHC substances | No |

Specifications and approvals

| | |
|-----------|--|
| Approvals | DNV GL |
| UL / CSA | UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076 |

Commercial data

| | |
|--------------------------------|--|
| Packaging size | 1 |
| Net weight | 209.8 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |
| eCl@ss | 27440202 Shell for industrial connectors |