

# Keystone Patch panel, loaded



Part number	20 82 405 0001
Specification	Keystone Patch panel, loaded
HARTING eCatalogue	https://b2b.harting.com/20824050001

### Identification

Category	Connector
Series	preLink <sup>®</sup>
Element	Patch panel

#### Version

Size	Keystone version
Fixing	In 19" racks acc. to IEC/DIN EN 60 297-3-100 (DIN 41 494-1)
Pack contents	24 preLink <sup>®</sup> RJ45 keystone jack 24 terminal modules for AWG 22 / 23 24 cable ties

# **Technical characteristics**

Limiting temperature	-40 +85 °C
Degree of protection acc. to IEC 60529	IP20
Transmission characteristics	Cat. 6 Class E up to 250 MHz
Data rate	10 Gbit/s

## Material properties

Material (insert)	Steel sheet
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No

Page 1 / 2 | Creation date 2019-09-19 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com



Material properties	
REACH SVHC substances	No
Specifications and approvals	
PROFINET	Yes
Commercial data	
Packaging size	1
Net weight	1,607.2 g
Country of origin	Germany
European customs tariff number	85389099
eCl@ss	27440292 Connector component (accessories)