

M12 CAT6a Bu gewinkelt VWM



Part number	21 03 381 4802
Specification	M12 CAT6a Bu gewinkelt VWM
HARTING eCatalogue	https://b2b.harting.com/21033814802

Identification

Category	Connectors
Series	Circular connectors M12
Element	PCB adapter
Specification	Angled incl. housing for front mounting

Version

Termination method	Reflow soldering termination (THR)
Gender	Female
Locking type	Screw locking PushPull
Shielding	Shielded
Number of contacts	8
Coding	X-coding
Pack contents	30 pieces in a tray

Technical characteristics

Rated current	0.5 A
Rated voltage	50 V
Rated impulse voltage	1.5 kV
Pollution degree	3
Insulation resistance	$>10^8 \Omega$
Contact resistance	$\leq 10 \text{ m}\Omega$
Ambient temperature	-40 ... +85 °C



Technical characteristics

Tightening torque	2 Nm Lock nut
Mating cycles	≥100
Degree of protection acc. to IEC 60529	IP65 / IP67 when mated
Transmission characteristics	Cat. 6 _A Class E _A up to 500 MHz
Overvoltage category	III
Isolation group	I (600 ≤ CTI)

Material properties

Material (insert)	Liquid crystal polymer (LCP)
Material (contacts)	Copper alloy
Surface (contacts)	Gold plated
Material (hood/housing)	Zinc die-cast
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	Yes
REACH SVHC substances	Lead

Specifications and approvals

Specifications	IEC 61076-2-109
UL / CSA	UL 1977 ECBT2.E102079 CSA-C22.2 No. 182.3 ECBT8.E102079
PROFINET	Yes

Commercial data

Packaging size	1
Net weight	32.73 g
Country of origin	Romania
European customs tariff number	85366990
eCl@ss	27440402 PCB connector