



Features

- Modularize mechanical design provides flexible product configuration and easy maintenance
- Available with auto-brightness sensor offers application in day and night
- Optional build-in touch screen for interactive application
- VGA connector with optional AV,SV,AV-Looping
- Complete custom design/solution for OEM customers

| | | | |
|---------------------|---|---|---|
| Panel | Cell Type / Glass Surface | TFT LCD / Black Anti-Glare, low reflection coating | |
| | Aspect Ratio / Size | Wide / 17.3" viewable diagonal area | |
| | Active Area / Pixel Pitch | 367.2(H) x 229.5(V) mm / 0.255(H) x 0.255(V) mm | |
| | Native Resolution / Colors | 1920(H) x 1080(V) / 262 K | |
| | Brightness / Contrast | 200 cd/m ² (typ) / 400 : 1 | |
| | Response Time | ≤ 16 ms | |
| | Viewing Angle (typical) | H. 90° (- 45° ~ + 45°) , V. 50° (- 30° ~ + 20°) | |
| | Light Source | LED , Long life, 50,000 hrs (typ) | |
| Input Sources | PC System | Signal | Analog RGB (0.7/1.0 V _{p-p} , 75 ohms) |
| | | Sync | Separate Sync, Composite Sync, Sync On Green |
| | | Frequency | F _h : 30 - 82Khz , F _v : 50 -75Hz |
| | Audio System | 2W Speaker x 2 | |
| Input Terminals | 1 x VGA (15 Pin Female D-Sub) , 1 x PC Audio (Stereo Headphone Jack) , 1 x AC Inlet | | |
| Convenient Features | Auto Calibration , Back Light Adjustment , Plug&Play (VESA DDC/CI, DDC 2B) | | |
| | OSD Multi-Languages , Wall Mount Ready (VESA 75 x 75 mm) | | |
| Power | Internal power supply with universal / Auto-Sensing, AC 90 to 260V, 50 / 60 Hz | | |
| Power Consumption | Operation / Power Saving | 22 watt , < 2 watt (Support DPMS) | |
| Operating Condition | Temperature / Humidity | 0° C ~ 50° C (32° F ~ 122° F) , 10% ~ 90% (no condensation) | |
| Storage Condition | Temperature / Humidity | - 20° C ~ 60° C (- 4° F ~ 140° F) , 10% ~ 90% (no condensation) | |
| Certification | | FCC , CE | |
| Dimensions | Physical | W x H x D = 485 x 345 x 58.8 mm | |
| | Carton | W x H x D = TBD | |
| Weight | N.W. / G.W. | 5.2 Kgs / 6.2 Kgs | |
| Container Loaded | 20ft / 40ft / 40ft HQ | TBD (Sets , By pallet) | |

| Options | Touch | Video / TV | Enhanced Panel | Others |
|---------|------------------|----------------------|--------------------------|------------------------------|
| | Resistive touch | SV + AV | Panel with LED backlight | Digital Signage(Stand alone) |
| | Capacitive touch | SV + AV + AV_Looping | High brightness panel | Networking Digital Signage |
| | SAW touch | SV + AV + TV | Wide Temperature | Motion Sensor |
| | Infrared touch | | Sunlight Readable | Light Sensor |
| | Protected glass | | | Auto-Dimming |