

IPM2316-UN40L0

Specification



Features

- Modularize mechanical design provides flexible product configuration and easy maintenance
- IP65 front side sealed for water-dust proof
- Optional panel with ultra high brightness and super dynamic contrast, along option with auto-brightness sensor offers application in day and night
- VGA connector with optional AV,SV,AV-Looping

| | | | |
|---------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------|---------------------------------------------------------|
| Panel | Cell Type / Glass Surface | TFT LCD / Black Anti-Glare, low reflection coating | |
| | Aspect Ratio / Size | 4:3 / 23.1" viewable diagonal area | |
| | Active Area / Pixel Pitch | 470.4(H) x 352.8(V) mm / 0.294(H) x 0.294(V) mm | |
| | Native Resolution / Colors | 1600(H) x 1200(V) / 16.7 Million | |
| | Brightness / Contrast | 400cd/m ² (typ) / 600 : 1 | |
| | Response Time | ≤ 8 ms | |
| | Viewing Angle (typical) | H. 160° (- 80° ~ + 80°) , V. 160°(- 80° ~ + 80°) | |
| | Light Source | LED , Long life, 35,000 hrs (typ) | |
| | Input Sources | PC System | Signal |
| Sync | | | Separate Sync, Composite Sync, Sync On Green |
| Frequency | | | F _h : 30 - 82Khz , F _v : 50 -75Hz |
| | Audio System | 3W Speaker x 2 | |
| Input Terminals | 1 x VGA (15 Pin Female D-Sub) , 1 x PC Audio (Stereo Headphone Jack) , 1 x AC Inlet | | |
| Convenient Features | Auto Calibration , Back Light Adjustment , Plug&Play (VESA DDC/CI, DDC 2B) | | |
| | OSD Multi-Languages , Wall Mount Ready (VESA 100 x 100 mm) | | |
| Power | Internal power supply with universal / Auto-Sensing, AC 90 to 260V, 50 / 60 Hz | | |
| Power Consumption | Operation / Power Saving | 110 watt , < 5 watt (Support DPMS) | |
| Operating Condition | Temperature / Humidity | 0°C ~ 50°C (32°F ~ 122°F) , 10% ~ 90% (no condensation) | |
| Storage Condition | Temperature / Humidity | - 20°C ~ 60°C (- 4°F ~ 140°F) , 10% ~ 90% (no condensation) | |
| Certification | FCC , CE | | |
| Dimensions | Physical | W x H x D = 638.0 x 543.4 x 97.0 (mm) | |
| | Carton | W x H x D = TBD | |
| Weight | N.W. / G.W. | 13.5 Kgs / 14.5 Kgs | |
| Container Loaded | 20ft / 40ft / 40ft HQ | TBD (Sets , By pallet) | |

| Options | Touch | Video / TV | Enhanced Panel | Others |
|---------|-----------------|----------------------|--------------------------|------------------------------|
| | Protected glass | SV + AV | Panel with LED backlight | Digital Signage(Stand alone) |
| | | SV + AV + AV_Looping | High brightness panel | Networking Digital Signage |
| | | SV + AV + TV | Wide Temperature | Motion Sensor |
| | | | Sunlight Readable | Light Sensor |
| | | | | Auto-Dimming |

Winsonic®

Winsonic Electronics CO.,LTD. TEL:886-3-3704789 FAX:886-3-3704722 E-mail:sales@ewinsonic.com
No.290-1 Wun-Jhong Rd. Taoyuan City, Taoyuan Taiwan R.O.C

Online Download

www.ewinsonic.com