

## Han E High Temp female contact 20 AWG

		Part number	09 33 800 6220
		Specification	Han E High Temp female contact 20 AWG
		HARTING eCatalogue	https://b2b.harting.com/09338006220
dentification			
Category	Contacts		
Series	Han E <sup>®</sup> High	ı Temp	
Type of contact	Crimp contac	Crimp contact	
Version			
Gender	Female		
Contact identification	No groove		
Technical characteristics			
	0.5 mm²		
Conductor cross-section	0.5 mm² AWG 20		
Conductor cross-section Conductor cross-section			
Technical characteristics Conductor cross-section Conductor cross-section Operating current Contact resistance	AWG 20		
Conductor cross-section Conductor cross-section Operating current	AWG 20 ≤16 A		
Conductor cross-section Conductor cross-section Operating current Contact resistance Stripping length	AWG 20 ≤16 A ≤1 mΩ		
Conductor cross-section Conductor cross-section Operating current Contact resistance Stripping length Material properties	AWG 20 ≤16 A ≤1 mΩ		
Conductor cross-section Conductor cross-section Operating current Contact resistance Stripping length Material properties Material (contacts)	AWG 20 ≤16 A ≤1 mΩ 7.5 mm		
Conductor cross-section Conductor cross-section Operating current Contact resistance Stripping length Material properties Material (contacts) Surface (contacts)	AWG 20 ≤16 A ≤1 mΩ 7.5 mm Copper alloy Silver plated		
Conductor cross-section Conductor cross-section Operating current Contact resistance Stripping length Material properties Material (contacts) Surface (contacts) RoHS	AWG 20 ≤16 A ≤1 mΩ 7.5 mm Copper alloy Silver plated compliant wi		lead by weight
Conductor cross-section Conductor cross-section Operating current Contact resistance Stripping length Material properties Material (contacts) Surface (contacts) RoHS RoHS exemptions	AWG 20 ≤16 A ≤1 mΩ 7.5 mm Copper alloy Silver plated compliant wi 6(c): Copper	th exemption	lead by weight
Conductor cross-section Conductor cross-section Operating current Contact resistance Stripping length Material properties Material (contacts) Surface (contacts) RoHS RoHS exemptions ELV status	AWG 20 ≤16 A ≤1 mΩ 7.5 mm Copper alloy Silver plated compliant wi 6(c): Copper	th exemption alloy containing up to 4 %	lead by weight
Conductor cross-section Conductor cross-section Operating current Contact resistance	AWG 20 ≤16 A ≤1 mΩ 7.5 mm Copper alloy Silver plated compliant wi 6(c): Copper	th exemption alloy containing up to 4 %	lead by weight

Page 1 / 2 | Creation date 2019-07-09 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric GmbH & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



## Material properties **REACH SVHC substances** Yes **REACH SVHC substances** Lead Specifications and approvals EN 60664-1 Specifications IEC 61984 Commercial data Packaging size 100 Net weight 1.62 g Country of origin Germany European customs tariff number 85366990 eCl@ss 27440204 Contact for industrial connectors

Page 2 / 2 | Creation date 2019-07-09 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric GmbH & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com