



Features

- 10.4" LCD panel, 800 x 600, 350 nits
- Intel® Atom N270 Processor
- Intel® 945GSE + ICH7M
- 1 x 200-pin DDR2 SO-DIMM up to 2GB DDR2 533 SDRAM
- 1xVGA, 2xUSB, 1xCOM, 1xLAN



| | | | |
|---------------|---------------------------|---|--|
| Panel | Cell Type / Glass Surface | TFT LCD / Black Anti-Glare, low reflection coating | |
| | Aspec Ratio / Size | 4 : 3 / 10.4" viewable diagonal area | |
| | Active Area / Pixel Pitch | 211.2(H) x 158.4(V) mm / 0.264(H) x 0.264(V) mm | |
| | Native Resolution / Color | 800(H) x 600(V) / 0.264(H) x 0.264(V) mm | |
| | Brignthess / Contrast | 350 cd/m ² (typ) / 600 : 1 | |
| | Response Time | ≤ 35 ms | |
| | Viewing Angle (Typical) | H. 140° (- 70° ~ + 70°) , V. 120°(- 60° ~ + 60°) | |
| | Light Source | CCFL, Long life, 50,000 hrs (typ) | |
| System | CPU | Intel Atom N270 ; FSB 533MHz, 45nm Processor | |
| | BIOS | Award 16MB SPI | |
| | System / Graphic Chipset | Intel® 945GSE + ICH7M / Graphic Media Accelerator 950 | |
| | System Memory | 1 x 200-pin DDR2 SO-DIMM up to 2GB DDR2 533 SDRAM | |
| | HDD | 2 x SATA | |
| | I/O Ports | 1 x VGA | |
| | | 2 x USB | |
| | | 1 x COM (RS232) | |
| 1 x LAN | | | |
| Expension | 1 x Mini PCI-e | | |
| Power | Power Input | DC 12V | |
| | Power Consumption | 26 Watt, <1 Watt | |
| Environmental | Operating Temperature | 0°C ~60°C (32°F~140°F) | |
| | Operating Humidity | 0%~95%(non-condensing) | |

| Options | Touch | Enhanced Pane | Other | |
|---------|-----------------------|-----------------------|-----------|----------------------------|
| | Resistive(With Glass) | High Brightness Panel | WiFi | Networking Digital Signage |
| | Capactive | Panel-LED Backlight | 3G | Web Cam |
| | SAW | Wide Temperature | Bluetooth | Motion Sensor |
| | | Wide Viewing Angle | RFID | Auto LightSensor |
| | | Sunlight Readable | | Auto-Dimming |