



### Features

- 10.1" LCD panel, 1024 x 600, 200 nits
- Intel® Atom N270 Processor
- Intel® 945GSE + ICH7M
- 1 x 200-pin DDR2 SO-DIMM up to 2GB DDR2 533 SDRAM
- 1xVGA, 2xUSB, 1xCOM, 1xLAN



Panel	Cell Type / Glass Surface	TFT LCD / Black Anti-Glare, low reflection coating	
	Aspec Ratio / Size	wide / 10.1" viewable diagonal area	
	Active Area / Pixel Pitch	222.72(H) x 125.28(V) mm / 0.2175(H) x 0.2088(V) mm	
	Native Resolution / Color	1024(H) x 600 (V) / 262 K	
	Brignthess / Contrast	200 cd/m <sup>2</sup> (typ) / 500:1	
	Response Time	≤ 16 ms	
	Viewing Angle (Typical)	H. 90° (- 45° ~ + 45°) , V. 50°(- 25° ~ + 25°)	
	Light Source	LED, Long life, 35,000 hrs (typ)	
System	CPU	Intel Atom N270 ; FSB 533MHz, 45nm Processor	
	BIOS	Award 16MB SPI	
	System / Graphic Chipset	Intel® 945GSE + ICH7M / Graphic Media Accelerator 950	
	System Memory	1 x 200-pin DDR2 SO-DIMM up to 2GB DDR2 533 SDRAM	
	HDD	2 x SATA	
	I/O Ports	1 x VGA	
		2 x USB	
		1 x COM (RS232)	
1 x LAN			
Expension	1 x Mini PCI-e		
Power	Power Input	DC 12V	
	Power Consumption	9 Watt, <1 Watt	
Environmental	Operating Temperature	0°C ~60°C (32°F~140°F)	
	Operating Humidity	0%~95%(non-condensing)	

Options	Touch	Enhanced Pane	Other	
	Resistive(With Glass)	High Brightness Panel	WiFi	Networking Digital Signage
	Capactive	Panel-LED Backlight	3G	Web Cam
	SAW	Wide Temperature	Bluetooth	Motion Sensor
		Wide Viewing Angle	RFID	Auto LightSensor
		Sunlight Readable		Auto-Dimming