



Features

- 17" LCD panel, 1280 x 1024, 300 nits
- Intel® Atom N270 Processor
- Intel @ 945GSE + ICH7M
- 1 x 200-pin DDR2 SO-DIMM up to 2GB DDR2 533 SDRAM
- 1xVGA, 4xUSB, 2xCOM, 2xLAN
- 1xK/B, 1xMouse, Mic-in, Line-in, Line-out



| | | |
|--------------------|---------------------------|--|
| Panel | Cell Type / Glass Surface | TFT LCD / Black Anti-Glare, low reflection coating |
| | Aspec Ratio / Size | 4 : 3 / 17" viewable diagonal area |
| | Active Area / Pixel Pitch | 337.92(H) x 270.34(V) mm / 0.264(H) x 0.264(V) mm |
| | Native Resolution / Color | 1280(H) x 1024(V) / 16.7 Million |
| | Brighthess / Contrast | 300 cd/m ² (typ) / 800 : 1 |
| | Response Time | ≤ 5 ms |
| | Viewing Angle (Typical) | H. 160° (- 80° ~ + 80°) , V. 160°(- 80° ~ + 80°) |
| | Light Source | CCFL, Long life, 50,000 hrs (typ) |
| System | CPU | Intel® Atom™ N270 ; FSB 533MHz, 45nm Processor |
| | BIOS | Award 16MB SPI |
| | System / Graphic Chipset | Intel @ 882945GSE/82801GBM + ICH7M |
| | System Memory | 1 x 200-pin DDR2 SO-DIMM up to 2GB DDR2 533 SDRAM |
| | HDD | 2 x SATA |
| | I/O Ports | 1 x VGA |
| | | 4 x USB |
| | | 2 x COM (RS232) |
| 2 x RJ45 | | |
| 1 x K/B; 1 x Mouse | | |
| | Mic-in, Line-in, Line-out | |
| Expension | 1 x Mini PCI-e | |
| Power | Power Input | 24V DC-IN(4-Din Connector) |
| | Power Consumption | 36 Watt, <1 Watt |
| Environmental | Operating Temperature | 0°C ~60°C (32°F~140°F) |
| | Operating Humidity | 0%~90%(non-condensing) |

| Options | Touch | Enhanced Pane | Other | |
|---------|-----------------------|-----------------------|-----------|----------------------------|
| | Resistive(With Glass) | High Brightness Panel | WiFi | Networking Digital Signage |
| | Capactive | Panel-LED Backlight | 3G | Web Cam |
| | SAW | Wide Temperature | Bluetooth | Motion Sensor |
| | | Wide Viewing Angle | RFID | Auto LightSensor |
| | | Sunlight Readable | | Auto-Dimming |