



### Features

- 10.1" LCD panel, 1024 x 600, 200 nits
- Intel® Atom N270 Processor
- Intel® 945GSE + ICH7M
- 1 x 200-pin DDR2 SO-DIMM up to 2GB DDR2 533 SDRAM
- 1xVGA, 2xUSB, 1xCOM, 1xLAN

|               |                           |   |
|---------------|---------------------------|---|
| Panel         | Cell Type / Glass Surface | TFT LCD / Black Anti-Glare, low reflection coating    |
|               | Aspec Ratio / Size        | wide / 10.1" viewable diagonal area                   |
|               | Active Area / Pixel Pitch | 222.72(H) x 125.28(V) mm / 0.2175(H) x 0.2088(V) mm   |
|               | Native Resolution / Color | 1024(H) x 600 (V) / 262 K                             |
|               | Brighthess / Contrast     | 200 cd/m <sup>2</sup> (typ) / 500:1                   |
|               | Response Time             | ≤ 16 ms   |
|               | Viewing Angle (Typical)   | H. 90° (- 45° ~ + 45°) , V. 50°(- 25° ~ + 25°)        |
|               | Light Source              | LED, Long life, 35,000 hrs (typ)                      |
| System        | CPU                       | Intel Atom N270 ; FSB 533MHz, 45nm Processor          |
|               | BIOS                      | Award 16MB SPI  |
|               | System / Graphic Chipset  | Intel® 945GSE + ICH7M / Graphic Media Accelerator 950 |
|               | System Memory             | 1 x 200-pin DDR2 SO-DIMM up to 2GB DDR2 533 SDRAM     |
|               | HDD                       | 2 x SATA  |
|               | I/O Ports                 | 1 x VGA   |
|               |                           | 2 x USB   |
|               |                           | 1 x COM (RS232)                                       |
|               |                           | 1 x LAN   |
| Power         | Expansion                 | 1 x Mini PCI-e  |
|               | Power Input               | DC 12V  |
| Environmental | Power Consumption         | 9 Watt, <1 Watt                                       |
|               | Operating Temperature     | 0°C ~60°C (32°F~140°F)                                |
| Environmental | Operating Humidity        | 0%~95%(non-condensing)                                |

|         |                       |                       |           |                            |
|---------|-----------------------|-----------------------|-----------|----------------------------|
| Options | Touch                 | Enhanced Pane         | Other     |                            |
|         | Resistive(With Glass) | High Brightness Panel | WiFi      | Networking Digital Signage |
|         | Capactive             | Panel-LED Backlight   | 3G        | Web Cam                    |
|         | SAW                   | Wide Temperature      | Bluetooth | Motion Sensor              |
|         |                       | Wide Viewing Angle    | RFID      | Auto LightSensor           |
|         |                       | Sunlight Readable     |           | Auto-Dimming               |