

CERTIFICATE OF COMPLIANCE

Certificate Number 20191025-E81956
Report Reference E81956-20190930
Issue Date 2019-OCTOBER-25

Issued to: TYCO Electronics Corp
2901 Fulling Mill Rd
Middletown PA 17057

**This certificate confirms that
representative samples of**

COMMUNICATIONS-, AUDIO/VIDEO-, DATA- AND
OTHER SIGNALING-CIRCUIT ACCESSORIES
M12 X-Code Field Installable Cable Plug,
Model Numbers 2327989-1 and 2327990-1.

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 1863, Communications-Circuit Accessories
CAN/CSA C22.2, No. 182.4-M90, Plugs, Receptacles and
Connectors for Communication Systems

Additional Information: See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



File E81956 Vol. 5 Sec. 20 Page 1 Issued: 2019-09-30
Vol. 40 Sec. 2
and Report

DESCRIPTION

PRODUCT COVERED:

USL, CNL M12 X-Code Field Installable Cable Plug, Model Numbers
2327989-1 and 2327990-1.

TECHNICAL CONSIDERATIONS (NOT FOR FIELD REPRESENTATIVE'S USE):

USL indicates evaluation to UL 1863, The Standard for Communications Circuit Accessories dated May 14th, 2004 including revisions through September 15th, 2016.

CNL indicates evaluation to CAN/CSA C22.2 No. 182.4, The Standard for Plugs, Receptacles, and Connectors for Communication Systems, 1st Edition, reaffirmed 2015.

RATINGS:

The products described in this Report are intended for data use only at 0.5A and 60VDC. For use with 22-26AWG wire.