

PPM32041-WH45C0-CB0J01

Panel-PC Panel Mount 32" 1920x1080, 450nits, Intel® Atom N270 Processor

Specification



Features

- 32" LCD panel, 1920 x 1080, 450 nits
- Intel® Atom N270 Processor
- Intel @ 945GSE + ICH7M
- 1 x 200-pin DDR2 SO-DIMM up to 2GB DDR2 533 SDRAM
- 1xVGA, 4xUSB, 2xCOM, 2xLAN
- 1xK/B, 1xMouse, Mic-in, Line-in, Line-out



Panel	Cell Type / Glass Surface	TFT LCD / Black Anti-Glare, low reflection coating	
	Aspec Ratio / Size	wide / 32" viewable diagonal area	
	Active Area / Pixel Pitch	698.4(H) x 392.9(V) mm / 0.3638(H) x 0.3638(V) mm	
	Native Resolution / Color	1920(H) x 1080(V) / 16.7 Million	
	Brighness / Contrast	450 cd/m ² (typ) / 5000 : 1	
	Response Time	≤ 6.5 ms(G-to-G)	
	Viewing Angle (Typical)	H. 178° (- 89° ~ + 89°) , V. 178°(- 89° ~ + 89°)	
	Light Source	CCFL, Long life, 50,000 hrs (typ)	
System	CPU	Intel® Atom™ N270 ; FSB 533MHz, 45nm Processor	
	BIOS	Award 16MB SPI	
	System / Graphic Chipset	Intel @ 882945GSE/82801GBM + ICH7M	
	System Memory	1 x 200-pin DDR2 SO-DIMM up to 2GB DDR2 533 SDRAM	
	HDD	2 x SATA	
	I/O Ports	1 x VGA	
		4 x USB	
		2 x COM (RS232)	
2 x RJ45			
1 x K/B; 1 x Mouse			
	Mic-in, Line-in, Line-out		
Expension	1 x Mini PCI-e		
Power	Power Input	24V DC-IN(4-Din Connector)	
	Power Consumption	151 Watt, <1 Watt	
Environmental	Operating Temperature	0°C~60°C (32°F~140°F)	
	Operating Humidity	0%~90%(non-condensing)	

Options	Touch	Enhanced Pane	Other	
	Resistive(With Glass)	High Brightness Panel	WiFi	Networking Digital Signage
	Capactive	Panel-LED Backlight	3G	Web Cam
	SAW	Wide Temperature	Bluetooth	Motion Sensor
		Wide Viewing Angle	RFID	Auto LightSensor
		Sunlight Readable		Auto-Dimming

Winsonic®

Winsonic Electronics CO.,LTD. TEL:886-3-3704789 FAX:886-3-3704722 E-mail:sales@ewinsonic.com
No.290-1 Wun-Jhong Rd. Taoyuan City, Taoyuan Taiwan R.O.C

Online Download

www.ewinsonic.com