



Features

- 15" LCD panel, 1024 x 768, 250 nits
- Intel® Atom N270 Processor
- Intel @ 945GSE + ICH7M
- 1 x 200-pin DDR2 SODIMM up to 2GB DDR2 533 SDRAM
- 1xVGA, 4xUSB, 2xCOM, 2xLAN
- 1xK/B, 1xMouse, Mic-in, Line-in, Line-out



Panel	Cell Type / Glass Surface	TFT LCD / Black Anti-Glare, low reflection coating	
	Aspec Ratio / Size	4 : 3 / 15" viewable diagonal area	
	Active Area / Pixel Pitch	304.13(H) x 228.10(V) mm / 0.297(H) x 0.297(V) mm	
	Native Resolution / Color	1024(H) x 768(V) / 16.2 Million	
	Brighness / Contrast	250 cd/m ² (typ) / 500 : 1	
	Response Time	≤ 12 ms	
	Viewing Angle (Typical)	H. 130° (- 65° ~ + 65°) , V. 100°(- 55° ~ + 45°)	
	Light Source	CCFL, Long life, 50,000 hrs (typ)	
System	CPU	Intel® Atom™ N270 ; FSB 533MHz, 45nm process technology	
	BIOS	Award 16MB SPI	
	System / Graphic Chipset	Intel @ 882945GSE/82801GBM + ICH7M	
	System Memory	1 x 200-pin DDR2 SODIMM up to 2GB DDR2 533 SDRAM	
	HDD	2 x SATA	
	I/O Ports	1 x VGA	
		4 x USB	
		2 x COM (RS232)	
2 x RJ45			
1 x K/B; 1 x Mouse			
	Mic-in, Line-in, Line-out		
Expension	1 x Mini PCI-e		
Power	Power Input	24V DC-IN(4-Din Connector)	
	Power Consumption	26 Watt, <1 Watt	
Environmental	Operating Temperature	0°C ~60°C (32°F~140°F)	
	Operating Humidity	0%~90%(non-condensing)	

Options	Touch	Enhanced Pane	Other	
	Resistive(With Glass)	High Brightness Panel	WiFi	Networking Digital Signage
	Capactive	Panel-LED Backlight	3G	Web Cam
	SAW	Wide Temperature	Bluetooth	Motion Sensor
		Wide Viewing Angle	RFID	Auto LightSensor
		Sunlight Readable		Auto-Dimming