

IPCH17W51-WU20L0-CB0J01

IP65 Panel-PC Chassis 17" 1920x1200, 200nits, Intel® Atom N270 Processor

Specification



Features

- 17" LED panel, 1920x1200, 200 nits
- Intel® Atom N270 Processor
- Intel @ 945GSE + ICH7M
- 1 x 200-pin DDR2 SO-DIMM up to 2GB DDR2 533 SDRAM
- 1xVGA, 4xUSB, 2xCOM, 2xLAN
- 1xK/B, 1xMouse, Mic-in, Line-in, Line-out



Panel	Cell Type / Glass Surface	LED / Black Anti-Glare, low reflection coating
	Aspec Ratio / Size	wide / 17" viewable diagonal area
	Active Area / Pixel Pitch	382.0(H) x 244.3(V) mm / 0.191(H) x 0.191(V) mm
	Native Resolution / Color	1920(H) x 1200(V) / 262 K
	Brignthess / Contrast	200 cd/m ² (typ) / 600 : 1
	Response Time	≤ 16 ms
	Viewing Angle (Typical)	H. 140° (- 70° ~ + 70°) , V. 120°(- 60° ~ + 60°)
	Light Source	LED, Long life, 50,000 hrs (typ)
System	CPU	Intel® Atom™ N270 ; FSB 533MHz, 45nm Processor
	BIOS	Award 16MB SPI
	System / Graphic Chipset	Intel @ 882945GSE/82801GBM + ICH7M
	System Memory	1 x 200-pin DDR2 SO-DIMM up to 2GB DDR2 533 SDRAM
	HDD	2 x SATA
	I/O Ports	1 x VGA
		4 x USB
		2 x COM (RS232)
2 x RJ45		
1 x K/B; 1 x Mouse		
	Mic-in, Line-in, Line-out	
Expension	1 x Mini PCI-e	
Power	Power Input	24V DC-IN(4-Din Connector)
	Power Consumption	28 Watt, <1 Watt
Environmental	Operating Temperature	0°C ~60°C (32°F~140°F)
	Operating Humidity	0%~90%(non-condensing)

Options	Touch	Enhanced Pane	Other	
	Resistive(With Glass)	High Brightness Panel	WiFi	Networking Digital Signage
	Capactive	Panel-LED Backlight	3G	Web Cam
	SAW	Wide Temperature	Bluetooth	Motion Sensor
		Wide Viewing Angle	RFID	Auto LightSensor
		Sunlight Readable		Auto-Dimming

Winsonic®

Winsonic Electronics CO.,LTD. TEL:886-3-3704789 FAX:886-3-3704722 E-mail:sales@ewinsonic.com
No.290-1 Wun-Jhong Rd. Taoyuan City, Taoyuan Taiwan R.O.C

Online Download

www.ewinsonic.com