

IPPM26041-WX50C0-CB0J01

IP65 Panel-PC Panel Mount 26" 1366x768, 500nits, Intel® Atom N270 Processor

Specification



Features

- 26" LCD panel, 1366 x 768, 500 nits
- Intel® Atom N270 Processor
- Intel® 945GSE + ICH7M
- 1 x 200-pin DDR2 SO-DIMM up to 2GB DDR2 533 SDRAM
- 1xVGA, 4xUSB, 2xCOM, 2xLAN
- 1xK/B, 1xMouse, Mic-in, Line-in, Line-out



Panel	Cell Type / Glass Surface	TFT LCD / Black Anti-Glare, low reflection coating	
	Aspec Ratio / Size	wide / 26" viewable diagonal area	
	Active Area / Pixel Pitch	575.77(H) x 323.71(V)mm / 0.42(H) x 0.42 (V)mm	
	Native Resolution / Color	1366(H) x 768 (V) / 16.7 Million	
	Brignthess / Contrast	500 cd/m ² (typ) / 800 : 1	
	Response Time	≤ 8 ms	
	Viewing Angle (Typical)	H. 176° (- 88° ~ + 88°) , V. 176°(- 88° ~ + 88°)	
	Light Source	CCFL, Long life, 50,000 hrs (typ)	
System	CPU	Intel® Atom™ N270 ; FSB 533MHz, 45nm Processor	
	BIOS	Award 16MB SPI	
	System / Graphic Chipset	Intel® 882945GSE/82801GBM + ICH7M	
	System Memory	1 x 200-pin DDR2 SO-DIMM up to 2GB DDR2 533 SDRAM	
	HDD	2 x SATA	
	I/O Ports	2 x COM (RS232)	
		1 x VGA	
		2 x RJ45	
		4 x USB	
		1 x K/B; 1 x Mouse	
		Mic-in, Line-in, Line-out	
	Expension	1 x Mini PCI-e	
Power	Power Input	24V DC-IN(4-Din Connector)	
	Power Consumption	91 Watt, <1 Watt	
Environmental	Operating Temperature	0°C ~60°C (32°F~140°F)	
	Operating Humidity	0%~90%(non-condensing)	

Options	Touch	Enhanced Pane	Other	
	Resistive(With Glass)	High Brightness Panel	WiFi	Networking Digital Signage
	Capactive	Panel-LED Backlight	3G	Web Cam
	SAW	Wide Temperature	Bluetooth	Motion Sensor
		Wide Viewing Angle	RFID	Auto LightSensor
		Sunlight Readable		Auto-Dimming

Winsonic®

Winsonic Electronics CO.,LTD. TEL:886-3-3704789 FAX:886-3-3704722 E-mail:sales@ewinsonic.com
No.290-1 Wun-Jhong Rd. Taoyuan City, Taoyuan Taiwan R.O.C

Online Download

www.ewinsonic.com